

Progressive Foam Technologies, Inc.
6753 Chestnut Ridge Road
Beach City, Ohio 44608
Toll Free 800-860-3626
Phone 330-756-3200
Fax 330-756-3206
Website www.fullback.com
E-mail info@progressivefoam.com

October 2009

Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) 3-Part Format, including *MasterFormat*, *SectionFormat*, and *PageFormat*, as described in *The Project Resource Manual—CSI Manual of Practice, Fifth Edition*.

This section must be carefully reviewed and edited by the Architect to meet the requirements of the project and local building code. Coordinate this section with other specification sections and the Drawings. Delete all “Specifier Notes” after editing this section.

Section numbers are from *MasterFormat 1995 Edition*, with section numbers from *MasterFormat 2004 Edition* in parentheses. Delete version not required.

SECTION 07210 (07 21 13.13)

VINYL SIDING INSULATION

Specifier Notes: This section covers Progressive Foam Technologies, Inc. “Fullback® Technology” custom-contoured foam board insulation factory laminated behind a specific make and profile of vinyl siding. Consult Progressive Foam Technologies, Inc. for assistance in editing this section for the specific application.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Contoured foam board insulation factory laminated behind vinyl siding.

1.2 RELATED REQUIREMENTS

Specifier Notes: Edit the following list of related sections as required. Delete related sections not required. List other sections with work directly related to this section.

- A. Section 07460 (07 46 34) – Insulated Vinyl Siding: Vinyl siding with factory-laminated board insulation.

1.3 REFERENCE STANDARDS

Specifier Notes: List reference standards mentioned in this section, complete with designations and titles. Delete reference standards not included in this edited section. This article does not require compliance with reference standards, but is merely a listing of those used.

- A. ASTM C 272 – Standard Test Method for Water Absorption of Core Materials for Structural Sandwich Constructions.
- B. ASTM C 303 – Standard Test Method for Dimensions and Density of Preformed Block and Board-Type Thermal Insulation.
- C. ASTM C 578 – Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation.
- D. ASTM E 84 – Standard Test Method for Surface Burning Characteristics of Building Materials.
- E. ASTM E 96 – Standard Test Methods for Water Vapor Transmission of Materials.
- F. UL 723 – Standard for Test for Surface Burning Characteristics of Building Materials.

1.4 SUBMITTALS

Specifier Notes: Edit submittal requirements as required. Delete submittals not required.

- A. Comply with Section 01330 (01 33 00) – Submittal Procedures.
- B. Product Data: Submit manufacturer's product data of board insulation.

Specifier Notes: Delete samples if not required.

- C. Samples: Submit manufacturer's sample of board insulation laminated to vinyl siding, minimum 6 inches by 6 inches.
- D. Manufacturer's Certification: Submit manufacturer's certification that board insulation complies with specified requirements and is suitable for intended application.
- E. Warranty Documentation: Submit manufacturer's standard warranty of board insulation.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Delivery and Acceptance Requirements: In accordance with insulated vinyl siding manufacturer's instructions.
- B. Storage and Handling Requirements: In accordance with insulated vinyl siding manufacturer's instructions.

PART 2 PRODUCTS

2.1 MANUFACTURER

- A. Progressive Foam Technologies, Inc., 6753 Chestnut Ridge Road, Beach City, Ohio 44608. Toll Free 800-860-3626. Phone 330-756-3200. Fax 330-756-3206. Website www.fullback.com. E-mail info@progressivefoam.com.

2.2 VINYL SIDING INSULATION

- A. Board Insulation: "Fullback Technology".
 - 1. Description: Custom-contoured foam board insulation factory laminated behind a specific make and profile of vinyl siding.
 - 2. Material:
 - a. Rigid expanded polystyrene (EPS), treated with fire retardant and insect deterrent.
 - b. Compliance: ASTM C 578.
 - c. Certification: UL 723.
 - 3. Density, ASTM C 303: 1.0 pcf (16 kg/m³).
 - 4. Surface Burning Characteristics, ASTM E 84:
 - a. Flame Spread Index: 5.
 - b. Smoke Developed Index: 100 to 200.
 - 5. Water Absorption, ASTM C 272: Maximum 2.75 percent by volume.
 - 6. Water Vapor Transmission, ASTM E 96: 5.0 perms/inch.
 - 7. Thermal Expansion, ASTM C 578: 0.000035 inch/inch/degree F (0.000063 mm/mm/degree C).
 - 8. R-Value: 2.2 to 5.1, depending on profile.
 - 9. Manufacturing Size Tolerances:
 - a. Thickness: Plus or minus 1/16 inch (1.6 mm).
 - b. Width: Plus or minus 1/8 inch (3.2 mm).
 - c. Length: Plus or minus 1/4 inch (6.4 mm).
 - 10. Profiles: Match vinyl siding profiles.
- B. Accessories:
 - 1. Vinyl Universal Underlayment Starter Strips: "EasyStart".
 - 2. New Construction Corner Post Insulation: "NC CornerPost".
 - 3. Starter adaptors.
 - 4. Window surrounds.
 - 5. Flat Foam Insulation: "Halfback".

Specifier Notes: Specify the section number for the insulated vinyl siding.

- C. Insulated Vinyl Siding: Specified in Section [07460] [07 46 34].

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine walls to receive vinyl siding with factory-laminated board insulation.
- B. Notify Architect of conditions that would adversely affect installation.
- C. Do not begin installation until unacceptable conditions are corrected.

3.2 INSTALLATION

- A. Install vinyl siding with factory-laminated board insulation in accordance with insulated vinyl siding manufacturer's instructions at locations indicated on the Drawings.

Specifier Notes: Specify the section number for the insulated vinyl siding.

- B. Insulated Vinyl Siding: Install insulated vinyl siding as specified in Section [07460] [07 46 34].

3.3 PROTECTION

- A. Protect installed vinyl siding with factory-laminated board insulation from damage during construction in accordance with insulated vinyl siding manufacturer's instructions.

END OF SECTION